


Teflex NP Black

- Pure PTFE
- PTFE is capable of running at high temperatures. Continuously operating at 300°C / 572°F with short term surges at 316°C / 600°F
- Can be used on products across the full pH scale, i.e. caustic and acid products will not effect PTFE
- Designed to dissipate electrical charge
- Food Grade - compliant to FDA & EU regulations

Note: Teflex NP is not recommended for use on oscillating applications. For vibrating applications, please discuss with your local BFM® Distributor.



PHYSICAL PROPERTIES:

Fibre	Pure PTFE
Colour	Black
Construction/Finish	Multilayer film
Weight	459 g/m ² 13.5 oz/yd ²
Thickness	0.23mm / 1/64"
Max. Operating Temp	300°C / 572°F
Max. Surge Temp	316°C / 600°F
Surface Resistivity (Ohms)	10 ⁶
Tensile Strength	263 N/50mm 30 lbs/inch
Tear Strength	97 N / 25lbs
Air Permeability	None

AVAILABLE SIZES: (in 50mm / 2" increments)

Diameter	Ø100mm - 500mm (also available in 125mm/5") (Ø4" - 20")
Length	80mm, 100mm - 1,000mm (3", 4" - 39 1/2")

(Size range is in mm, so inch conversions are approximate only. Restrictions apply for larger diameters, or when TR versions used. Refer to [Connector Sizes](#) for more information)

COMPLIANCE:

Atex Compliant: IBExU tested. Can be used in all dust & gas explosion hazardous areas (restrictions apply).

Complies with the following regulations:
 FDA 21 CFR 177.1550, 175.105 & 178.3297,
 (EC) 1935/2004 & 10/2011,